



A410

AC Contour Probe

The A410 Contour Probe is a rugged high performance instrument designed for Magnetic Particle inspection to accepted Nondestructive testing standards.

Parker Contour Probes are designed with flexible legs that allow the field to be "focused" at a precise area of inspection. Components are protected by a reinforced glass-filled nylon housing. Model A410 and A410S produce a strong constant AC field.

Plastic carry cases (PL-Case & C-Case) and Test Kits (PL-A Kit & A Kit) are available. Standard test kits include 1 lb. each of Red & Gray powder, PB1 powder blower, and carrying case.

Features

High-impact, glass-filled nylon housing AC Only

One year repair/replacement guarantee Exceeds ASTM lifting standards

Standards Compliance

IP51

ASME Section V, Article 7

ASTM E709

ASTM E1444

ASTM E3024

EN ISO 9934-3 (230V Only)

CE (Optional - 230V Only)



Applications

Defect location: Surface

Ideal for:

Field Testing

Spot Inspections

In-service Inspections

Demanding Environments

Welding Inspections

Defect Examples:

Inclusions

Seams

Shrink cracks

Tears

Laps

Welding slags

Grinding cracks

Quenching cracks

Fatigue cracks



Product Properties

Weight	8 lbs. (3.6 kg)
Leg Span	0 – 12 in (0 – 304.8 mm)
Cord Length	10 ft. (3.048 m)
Duty Cycle	50%
Electrical Requirements	115VAC – 60 Hz : 6 Amps 230VAC – 50/60 Hz : 3 Amps

Use Recommendations

NDT Method	Magnetic Particle Testing
Recommended	Weight Lift Test Bar – TB10
Accessories	Yoke Light – Y400

Part Numbers

A410 - 115VAC

A410S - 230VAC

CDMX



