

## **B300MR**

# **AC Contour Probe**

The B300MR Contour Probe is a rugged high performance instrument designed for Magnetic Particle inspection to accepted Nondestructive testing standards.

Parker Contour Probes are designed with flexible legs that allow the field to be "focused" at a precise area of inspection. Components are protected by a reinforced glass-filled nylon housing. The external push button switch magnetically activates the power circuit from the outside. There is no electrical contact between the switch and internal circuit. This instrument is ideally suited for high moisture areas. Model B300MR and B300MRS produce a strong constant AC field.

Plastic carry cases (PL-Case & C-Case) and Test Kits (PL-A Kit & A Kit) are available. Standard test kits include 1 lb. each of Red & Gray powder, PB1 powder blower, and carrying case.

#### <u>Features</u>

High-impact, glass-filled nylon housing AC Only One year repair/replacement guarantee Exceeds ASTM lifting standards

Standards Compliance

IP65
ASME Section V, Article 7
ASTM E709
ASTM E1444
ASTM E3024
EN ISO 9934-3 (230V Only)



## <u>Applications</u>

**Defect location**: Surface

#### Ideal for:

Field Testing
Spot Inspections
In-service Inspections
Demanding Environments
Welding Inspections

## **Defect Examples:**

Inclusions
Seams
Shrink cracks
Tears
Laps
Welding slags
Grinding cracks
Quenching cracks

Fatigue cracks



# **Product Properties**

Weight	7 lbs. (3.18 kg)
Leg Span	0 – 12 in (0 – 304.8 mm)
Cord Length	10 ft. (3.048 m)
Duty Cycle	50%
Electrical Requirements	115VAC – 60 Hz : 6 Amps 230VAC – 50/60 Hz : 3 Amps

# **Use Recommendations**

NDT Method	Magnetic Particle Testing
Recommended	Weight Lift Test Bar – TB10
Accessories	Yoke Light – Y300

## Part Numbers

B300MR - 115VAC

B300MRS - 230VAC

#### $\mathsf{CDMX}$

