

Features:

- 3.5" LCD Display
- Support Video Recording (MPEG4)
- Support Snapshot (JPEG format)
- Support replay video and image
- Support rotated lens tube - allows user to capture magnified images at any angle
- Includes a 1 GB SD card for storing video and images and editing on a PC
- With 16 operation languages software
- Support AV out (PAL/NTSC selectable)
- Working temperature -20o to 60o (Celsius)
- Power charger indication light
- Portable battery design allowing user to change battery at any time
- With USB port (1.2/2.0) allowing PC transfer
- Adjustable illumination LED light



Insertion Tube and Light Source

- Resolution (Dynamic Static):
VGA resolution provides real 640x480
- Size Tip (Insert Tube) Diameter: 5.5mm / 4.3mm (Optional)
- Tube Length: from 1 meter to 30 meters
- Field of View (FOV): 67o
- Depth of View (DOV) 1.0 cm to infinity
- Light Source: 4 LED (OD 5.5mm)
- Probe Working Temperature: -20o to 60o C
- Ingress Protection: IP 57 (OD 5.5mm)

Display Unit

- Power: DC 5V
- Display: 3.5" TFT LCD Monitor
- Interface: USB (1.1/2.0)
- AV out (PAL/NTSC selectable)
- Battery: Rechargeable Li-ion Battery
- Power Charger: 100~240V AC in / 5.5V DC out
- Reset

Interchangeable camera lengths and diameters

OD 4.3mm DOF 1Cm
1M
2M
3M
5M
10M
OD 5.5mm DOF 1Cm
1M
2M
3M
5M
10M
20M
30M
OD 8mm DOF 8cm or 1CM
1M
2M
3M
OD 10mm DOF 8cm or 2CM
1M
2M
3M



CDMX

Av. 517 No. 80, Col San Juan de Aragón 1a Sección, C.P. 07969, Alc. Gustavo A. Madero, México, CDMX.

(55) 5751 3787
(55) 5751 3767

Apodaca N.L.

Olimpia 1424 B Col. Nueva Lindavista, N.L. CP 67129

(81) 13672397
(81) 13574285

in f @
Ensayos No Destructivos

